

# City Street Construction Guidelines

Version 1.4 Dt. 10.07.10



## Purpose

These guidelines have been created to enforce a consistent and coordinated design for all citywide capital project signs and to communicate the shared citywide goals of the City's ten-year Capital Plan.

## Font usage

The fonts represented in this guideline are vital to the cohesiveness of the ONESF campaign and should not be deviated from. The font size, leading and kerning have all been pre-selected for optimum viewing from maximum viewing distances. Kerning may be adjusted in order to fit the appropriate copy within editing reason. Only mandatory information for public consumption is preferable. Prior to beginning your signage project, install the fonts used in this guide from your Capital Plan sign guideline package prior to creating a new sign.

## Font descriptions

The first number in the font description is the "font size" and the second is the "leading" (example: 306pt/288pt). Font "type" or "face" is defined by the first description and the second description is the "style" (example: Gill Sans/Regular).

## What logos can I use?

Only logos from client City departments, significant fiscal sponsors, or City departments who have contracting authority for the delivery of the project shall be included on the sign. This does not include the logos for private architects, engineers, general contractors or subcontractors. The client department logo shall be placed directly below the "This project is brought to you by:" All other logos shall be placed to the left of the client department logo on the same axis, or stacked to the left and below the client department logo if there are more than three logos. For instance, a San Francisco Public Library (SFPL) district library designed and managed by the Department of Public Works (DPW) with significant financial support from the Friends of the San Francisco Public Library (FSFPL) would have the SFPL logo below "This project is brought to you by:" with the DPW and FSFPL logos to the left.

**Dimensions:** Total width 72". Top margins: 3.25", 6.875", 2.25", 22.25" approx., 37.25", 3.25". Left margins: 1.5", 6.875", 1.625", 2". Vertical spacing: 1.5", 22.25", 48" total height, 1.875", 1.5", 8.25", 1.5".

**Callouts:**

- 1: Use only approved ONESF logo.
- 2: Optional: Designation # 100pt/180pt Gill Sans/Reg 0 Kerning
- 104pt/124pt Franklin Gothic Medium/Regular - 0 Kerning
- 78pt/94pt Gill Sans/Regular -25 Kerning
- 35pt/46pt Franklin Gothic Medium/Regular - 0 Kerning
- 37pt/46pt Franklin Gothic Medium/Regular - 0 Kerning
- 35pt/46pt Franklin Gothic Medium/Regular - 0 Kerning
- 34pt/40pt Franklin Gothic Medium/Regular - 0 Kerning


**Font Descriptions:**

- Left Aligned: 306pt/288pt Gill Sans/Regular -34 Kerning
- 216pt/288pt Gill Sans/Regular -25 Kerning
- 144pt/180pt Gill Sans/Regular 0 Kerning
- 72pt/135pt Gill Sans/Regular 0 Kerning
- 117pt/134pt Gill Sans/Regular 0 Kerning
- 162pt/153pt Myriad Pro/Bold 0 Kerning
- 126pt/92pt Myriad Pro/Semibold 0 Kerning
- 90pt/92pt Myriad Pro/Semibold 0 Kerning

**Printing Specifications:** Strict adherence to the printing specifications should be followed. Do not deviate from the specifications below. Vinyl may only be used indoors and not in direct sunlight.

All signs should last at least 3 years using the minimum requirements below.  
**Mounting Material - Medium Density Overlay:** MDO board is a wood panel. It is usually made of plywood, coated with outer layers of resin-impregnated kraft paper. Thickness are 1/2 and 3/4 inch. Recommend Crezon® Two Step®.  
**Coatings - UV coating:** UV and Anti-Graffiti coatings should last at least 3 years.  
**Laminate - Anti-Graffiti laminate:** Any brand will work. Only swift removal of graffiti can ensure this laminates durability.  
**Color - 4-color printing:** All colors should be printed on a 4-color CMYK printer.

**OPTIONAL:** Gray or Black may be used for the footer at the discretion of the author.



**PANTONE**®  
Cool Gray 4 C

**PANTONE:** PMS  
Cool Gray 4 C  
CMYK: 24K  
RGB: 201R, 202G, 204B  
HEX: C9CACC

**Additional Logos:** Additional logos may be used as long as they are 1-color (white) and proportionally equal and horizontally spaced 1/2 logo apart. For 3 and 4 logos groups, see below for allowable examples. Logo Hierarchy is discouraged.

